




Transient voltage suppressors

peak pulse power 600W Breakdown voltage 6.8 to 550V

Features


- ◆ Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- ◆ Glass passivated junction
- ◆ 600W peak pulse power capability with a 10/1000us waveform, repetition rate (duty cycle): 0.01%
- ◆ Excellent clamping capability
- ◆ Low incremental surge resistance
- ◆ Very fast response time
- ◆ High temp. soldering guaranteed: 265°C/10 seconds, 0.375" (9.5mm) lead length, 5lbs. (2.3 kg) tension



DO-204AC (DO-15)

Mechanical Data

- ◆ Case: JEDEC DO-204AC(DO-15) molded plastic body over passivated junction
- ◆ Terminals: Solder plated axial leads, solderable per MIL-STD-750, Method 2026
- ◆ Polarity: For unidirectional types the color band denotes the cathode, which is positive with respect to the anode under normal TVS operation
- ◆ Mounting Position: Any
- ◆ Weight: 0.015oz., 0.4g



Dimensions in inches and (millimeters)

Devices for Bidirectional Applications

For bi-directional devices, use suffix C or CA for types P6KE6.8 through types P6KE440 (e.g. P6KE6.8C, P6KE440CA). Electrical characteristics apply in both directions.

Maximum Ratings and Characteristics

($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Peak power dissipation with a 10/1000us waveform (Fig. 1)	P_{PPM}	Minimum 600 ⁽¹⁾	W
Peak pulse current with a 10/1000us waveform ⁽¹⁾	I_{PPM}	See Next Table	A
Steady state power dissipation at $T_A=75^\circ\text{C}$, lead lengths 0.375" (9.5mm) ⁽²⁾	P_{MAV}	5.0	W
Peak forward surge current, 0.3ms single half sine-wave ⁽³⁾	I_{FSM}	100	A
Maximum instantaneous forward voltage at 50A for unidirectional only ⁽⁴⁾	V_F	3.5/5.0	Volts
Typical thermal resistance junction-to-lead	$R_{\theta JL}$	20	$^\circ\text{C/W}$
Typical thermal resistance junction-to-ambient	$R_{\theta JA}$	75	$^\circ\text{C/W}$
Operating junction and storage temperature range	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$

- Notes: 1. Non-repetitive current pulse, per Fig.3 and derated above $T_A=25^\circ\text{C}$ per Fig. 2
 2. Mounted on copper pad area of 1.6 x 1.6" (40 x 40mm) per Fig. 5
 3. Measured on 0.3ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum
 4. $V_F=3.5\text{ V}$ for devices of $V_{BR}<220\text{V}$, and $V_F=5.0\text{ Volt max.}$ for devices of $V_{BR}>220\text{V}$



Taiwan Goodark Technology Co.,Ltd

P6KE6.8 Thru P6KE550CA

Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified.)

Device type	Breakdown voltage $V_{(BR)}$ (Volts) ⁽¹⁾		Test current at I_T (mA)	Stand-off voltage V_{WM} (Volts)	Maximum reverse leakage at V_{WM} $I_{o(2)}$ (uA)	Maximum peak pulse current $I_{PPM(2)}$ (A)	Maximum clamping voltage at I_{PPM} V_c (Volts)	Maximum temperature coefficient of $V_{(BR)}$ (% / °C)
	Min.	Max.						
P6KE6.8	6.12	7.48	10	5.50	1000	55.6	10.8	0.057
P6KE6.8A	6.45	7.14	10	5.80	1000	57.1	10.5	0.057
P6KE7.5	6.75	8.25	10	6.05	500	51.3	11.7	0.061
P6KE7.5A	7.13	7.88	10	6.40	500	53.1	11.3	0.061
P6KE8.2	7.38	9.02	10	6.63	200	48.0	12.5	0.065
P6KE8.2A	7.79	8.61	10	7.02	200	49.6	12.1	0.065
P6KE9.1	8.19	10.0	1.0	7.37	50	43.5	13.8	0.068
P6KE9.1A	8.65	9.55	1.0	7.78	50	44.8	13.4	0.068
P6KE10	9.00	11.0	1.0	8.10	10	40.0	15.0	0.073
P6KE10A	9.50	10.5	1.0	8.55	10	41.4	14.5	0.073
P6KE11	9.90	12.1	1.0	8.92	5.0	37.0	16.2	0.075
P6KE11A	10.5	11.6	1.0	9.40	5.0	38.5	15.6	0.075
P6KE12	10.8	13.2	1.0	9.72	5.0	34.7	17.3	0.076
P6KE12A	11.4	12.6	1.0	10.2	5.0	35.9	16.7	0.078
P6KE13	11.7	14.3	1.0	10.5	5.0	31.6	19.0	0.081
P6KE13A	12.4	13.7	1.0	11.1	5.0	33.0	18.2	0.081
P6KE15	13.5	16.5	1.0	12.1	1.0	27.3	22.0	0.084
P6KE15A	14.3	15.8	1.0	12.8	1.0	28.3	21.2	0.084
P6KE16	14.4	17.6	1.0	12.9	1.0	25.5	23.5	0.086
P6KE16A	15.2	16.8	1.0	13.6	1.0	26.7	22.5	0.086
P6KE18	16.2	19.8	1.0	14.5	1.0	22.6	26.5	0.088
P6KE18A	17.1	18.9	1.0	15.3	1.0	23.8	25.2	0.088
P6KE20	18.0	22.0	1.0	16.2	1.0	20.6	29.1	0.090
P6KE20A	19.0	21.0	1.0	17.1	1.0	21.7	27.7	0.090
P6KE22	19.8	24.2	1.0	17.8	1.0	18.8	31.9	0.092
P6KE22A	20.9	23.1	1.0	18.8	1.0	19.6	30.6	0.092
P6KE24	21.6	26.4	1.0	19.4	1.0	17.3	34.7	0.094
P6KE24A	22.8	25.2	1.0	20.5	1.0	18.1	33.2	0.094
P6KE27	24.3	29.7	1.0	21.8	1.0	15.3	39.1	0.096
P6KE27A	25.7	28.4	1.0	23.1	1.0	16.0	37.5	0.096
P6KE30	27.0	33.0	1.0	24.3	1.0	13.8	43.5	0.097
P6KE30A	28.5	31.5	1.0	25.6	1.0	14.5	41.4	0.097
P6KE33	29.7	36.3	1.0	26.8	1.0	12.6	47.7	0.098
P6KE33A	31.4	34.7	1.0	28.2	1.0	13.1	45.7	0.098
P6KE36	32.4	39.6	1.0	29.1	1.0	11.5	52.0	0.099
P6KE36A	34.2	37.8	1.0	30.8	1.0	12.0	49.9	0.099
P6KE39	35.1	42.9	1.0	31.6	1.0	10.6	56.4	0.100
P6KE39A	37.1	41.0	1.0	33.3	1.0	11.1	53.9	0.100
P6KE43	38.7	47.3	1.0	34.8	1.0	9.7	61.9	0.101
P6KE43A	40.9	45.2	1.0	36.8	1.0	10.1	59.3	0.101
P6KE47	42.3	51.7	1.0	38.1	1.0	8.8	67.8	0.101
P6KE47A	44.7	49.4	1.0	40.2	1.0	9.3	64.8	0.101
P6KE51	45.9	56.1	1.0	41.3	1.0	8.2	73.5	0.102
P6KE51A	48.5	53.6	1.0	43.6	1.0	8.6	70.1	0.102
P6KE56	50.4	61.6	1.0	45.4	1.0	7.5	80.5	0.103
P6KE56A	53.2	58.8	1.0	47.8	1.0	7.8	77.0	0.103



Taiwan Goodark Technology Co.,Ltd

P6KE6.8 Thru P6KE550CA

Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified.)

Device type	Breakdown voltage V_{BR} (Volts) ⁽¹⁾		Test current at I_T (mA)	Stand-off voltage V_{WM} (Volts)	Maximum reverse leakage at V_{WM} I_D ⁽²⁾ (μ A)	Maximum peak pulse current I_{PPM} ⁽²⁾ (A)	Maximum clamping voltage at V_C (Volts)	Maximum temperature coefficient of V_{BR} (% / °C)
	Min.	Max.						
P6KE6.8	55.8	68.2	1.0	50.2	1.0	6.7	89.0	0.104
P6KE6.8A	58.9	65.1	1.0	53.0	1.0	7.1	85.0	0.104
P6KE8.8	61.2	74.8	1.0	55.1	1.0	6.1	98.0	0.104
P6KE8.8A	64.6	71.4	1.0	58.1	1.0	6.5	92.0	0.104
P6KE7.5	67.5	82.5	1.0	60.7	1.0	5.6	108	0.105
P6KE7.5A	71.3	78.8	1.0	64.1	1.0	5.8	103	0.105
P6KE8.2	73.8	90.2	1.0	66.4	1.0	5.1	118	0.105
P6KE8.2A	77.9	86.1	1.0	70.1	1.0	5.3	113	0.105
P6KE9.1	81.9	100	1.0	73.7	1.0	4.6	131	0.106
P6KE9.1A	88.5	95.5	1.0	77.8	1.0	4.8	125	0.106
P6KE10.0	90.0	110	1.0	81.0	1.0	4.2	144	0.106
P6KE10.0A	95.0	105	1.0	85.5	1.0	4.4	137	0.106
P6KE11.0	99.0	121	1.0	89.2	1.0	3.8	158	0.107
P6KE11.0A	105	118	1.0	94.0	1.0	3.9	152	0.107
P6KE12.0	108	132	1.0	97.2	1.0	3.5	173	0.107
P6KE12.0A	114	126	1.0	102	1.0	3.6	165	0.107
P6KE13.0	117	143	1.0	105	1.0	3.2	187	0.107
P6KE13.0A	124	137	1.0	111	1.0	3.4	179	0.107
P6KE15.0	135	165	1.0	121	1.0	2.8	215	0.108
P6KE15.0A	143	158	1.0	128	1.0	2.9	207	0.108
P6KE16.0	144	176	1.0	130	1.0	2.6	230	0.108
P6KE16.0A	152	168	1.0	136	1.0	2.7	219	0.108
P6KE17.0	153	187	1.0	138	1.0	2.5	244	0.108
P6KE17.0A	162	179	1.0	145	1.0	2.6	234	0.108
P6KE18.0	162	198	1.0	146	1.0	2.3	258	0.108
P6KE18.0A	171	189	1.0	154	1.0	2.4	246	0.108
P6KE20.0	180	220	1.0	162	1.0	2.1	287	0.108
P6KE20.0A	190	210	1.0	171	1.0	2.2	274	0.108
P6KE22.0	198	242	1.0	175	1.0	1.7	344	0.108
P6KE22.0A	209	231	1.0	185	1.0	1.8	328	0.108
P6KE25.0	225	275	1.0	202	1.0	1.7	360	0.110
P6KE25.0A	237	263	1.0	214	1.0	1.7	344	0.110
P6KE30.0	270	330	1.0	243	1.0	1.4	430	0.110
P6KE30.0A	285	315	1.0	256	1.0	1.4	414	0.110
P6KE35.0	315	385	1.0	284	1.0	1.2	504	0.110
P6KE35.0A	333	368	1.0	300	1.0	1.2	482	0.110
P6KE40.0	360	440	1.0	324	1.0	1.0	574	0.110
P6KE40.0A	380	420	1.0	342	1.0	1.1	548	0.110
P6KE44.0	396	484	1.0	356	1.0	0.95	631	0.110
P6KE44.0A	418	462	1.0	376	1.0	1.0	602	0.110
P6KE48.0A	456	504	1.0	408	1.0	0.9	658	0.110
P6KE51.0A	485	535	1.0	434	1.0	0.9	698	0.110
P6KE53.0A	503.5	556.5	1.0	450	1.0	0.8	725	0.110
P6KE54.0A	513	567	1.0	459	1.0	0.8	740	0.110
P6KE55.0A	522.5	577.5	1.0	467	1.0	0.8	760	0.110

Notes: 1. V_{BR} measured after I_T applied for 300 μ s, I_T =square wave pulse or equivalent

2. Surge current waveform per Fig. 3 and derate per Fig. 2

3. For bidirectional types with V_{WM} of 10 volts and less, the I_D limit is doubled

4. All terms and symbols are consistent with ANSI/IEEE C62.35

5. For parts without A, the V_{BR} is +10%

Description:

This P6KE TVS series is a low cost commercial product for use in applications where large voltage transients can permanently damage voltage-sensitive components.

The P6KE series device types are designed in a small package size where power and space is a consideration. They are characterized by their high surge capability, extremely fast response time, and low impedance, (Ron). Because of the unpredictable nature of transients, and the variation of the impedance with respect to these transients, impedance, per se, is not specified as a parametric value. However, a minimum voltage at low current conditions (BV) and a maximum clamping voltage (Vc) at a maximum peak pulse current is specified.

In some instances, the thermal effect (see Vc Clamping Voltage) may be responsible for 50% to 70% of the observed voltage differential when subjected to high current pulses for several duty cycles, thus making a maximum impedance specification insignificant.

In case of a severe current overload or abnormal transient beyond the maximum ratings, the Transient Voltage Suppressor will initially fail 'short' thus tripping the system's circuit breaker or fuse while protecting the entire circuit. Curves depicting clamping voltage vs. various current pulses are available from the factory.

Extended power curves vs. pulse time are also available.



RATINGS AND CHARACTERISTIC CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

