



## TGD N-Channel Enhancement Mode Power MOSFET

**Description**

The TGD20H18 uses advanced trench technology and design to provide excellent  $R_{DS(ON)}$  with low gate charge. It can be used in a wide variety of applications.

**General Features**


- $V_{DS} = 20V, I_D = 185A$
- $R_{DS(ON)} < 2.0 \text{ m}\Omega @ V_{GS}=4.5V$
- $R_{DS(ON)} < 2.4 \text{ m}\Omega @ V_{GS}=2.5V$
- High density cell design for ultra low  $R_{DS(on)}$
- Fully characterized avalanche voltage and current
- Good stability and uniformity with high  $E_{AS}$
- Excellent package for good heat dissipation
- Special process technology for high ESD capability

**Application**


- Power switching application
- Hard switched and high frequency circuits
- Uninterruptible power supply

**100% UIS TESTED!**


**100%  $\Delta V_{ds}$  TESTED!**



Schematic diagram



pin assignment



TO-220-3L top view

**Package Marking and Ordering Information**

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
TGD30H15	TGD30H15	TO-220-3L	-	-	-

**Absolute Maximum Ratings ( $T_C=25^\circ\text{C}$  unless otherwise noted)**

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	$V_{DS}$	20	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$	V
Drain Current-Continuous	$I_D$	185	A
Drain Current-Continuous( $T_C=100^\circ\text{C}$ )	$I_D (100^\circ\text{C})$	130	A
Pulsed Drain Current	$I_{DM}$	400	A
Maximum Power Dissipation	$P_D$	130	W
Derating factor		0.87	$\text{W}/^\circ\text{C}$
Single pulse avalanche energy (Note 5)	$E_{AS}$	1700	mJ



Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 To 175	°C
--	-----------------------------------	------------	----

**Thermal Characteristic**




Thermal Resistance,Junction-to-Case <sup>(Note 2)</sup>	R <sub>θJC</sub>	1.15	°C/W
---	------------------	------	------







**Electrical Characteristics (T<sub>C</sub>=25 °C unless otherwise noted)**

Parameter	Symbol	Condition	Min	Typ	Max	Unit
<b>Off Characteristics</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	V <sub>GS</sub> =0V I <sub>D</sub> =250μA	20	-	-	V
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> =20V, V <sub>GS</sub> =0V	-	-	1	μA
Gate-Body Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> =±12V, V <sub>DS</sub> =0V	-	-	±100	nA
<b>On Characteristics</b> <sup>(Note 3)</sup>						
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	0.5	0.75	1.2	V
Drain-Source On-State Resistance	R <sub>DS(ON)</sub>	V <sub>GS</sub> =4.5V, I <sub>D</sub> =20A	-	1.4	2.0	mΩ
		V <sub>GS</sub> =2.5V, I <sub>D</sub> =15A		1.6	2.4	
Forward Transconductance	g <sub>FS</sub>	V <sub>DS</sub> =5V, I <sub>D</sub> =20A	100	-	-	S
<b>Dynamic Characteristics</b> <sup>(Note 4)</sup>						
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> =10V, V <sub>GS</sub> =0V, F=1.0MHz	-	5000	-	PF
Output Capacitance	C <sub>oss</sub>		-	1200	-	PF
Reverse Transfer Capacitance	C <sub>rss</sub>		-	900	-	PF
<b>Switching Characteristics</b> <sup>(Note 4)</sup>						
Turn-on Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> =10V, I <sub>D</sub> =2A, R <sub>L</sub> =15Ω V <sub>GS</sub> =10V, R <sub>G</sub> =2.5Ω	-	12	-	nS
Turn-on Rise Time	t <sub>r</sub>		-	13	-	nS
Turn-Off Delay Time	t <sub>d(off)</sub>		-	45	-	nS
Turn-Off Fall Time	t <sub>f</sub>		-	32	-	nS
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> =10V, I <sub>D</sub> =20A, V <sub>GS</sub> =10V	-	70	-	nC
Gate-Source Charge	Q <sub>gs</sub>		-	16	-	nC
Gate-Drain Charge	Q <sub>gd</sub>		-	20	-	nC
<b>Drain-Source Diode Characteristics</b>						
Diode Forward Voltage <sup>(Note 3)</sup>	V <sub>SD</sub>	V <sub>GS</sub> =0V, I <sub>S</sub> =20A	-		1.2	V
Diode Forward Current <sup>(Note 2)</sup>	I <sub>S</sub>		-	-	150	A
Reverse Recovery Time	t <sub>rr</sub>	T <sub>J</sub> = 25°C, IF = 20A di/dt = 100A/μs <sup>(Note 3)</sup>	-	49	-	nS
Reverse Recovery Charge	Q <sub>rr</sub>		-	66	-	nC
Forward Turn-On Time	t <sub>on</sub>	Intrinsic turn-on time is negligible (turn-on is dominated by LS+LD)				

**Notes:**

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
  2. Surface Mounted on FR4 Board, t ≤ 10 sec.
  3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
  4. Guaranteed by design, not subject to production
5. E<sub>AS</sub> condition : T<sub>j</sub>=25°C, V<sub>DD</sub>=20V, V<sub>G</sub>=10V, L=1mH, R<sub>g</sub>=25Ω, I<sub>AS</sub>=58.5A

**Test circuit**
**1) E<sub>AS</sub> Test Circuit**

**2) Gate Charge Test Circuit**

**3) Switch Time Test Circuit**


**Typical Electrical and Thermal Characteristics (Curves)**

**Figure 1 Output Characteristics**

**Figure 4 Rdson-JunctionTemperature**

**Figure 2 Transfer Characteristics**

**Figure 5 Gate Charge**

**Figure 3 Rdson- Drain Current**

**Figure 6 Source- Drain Diode Forward**




Figure 7 Capacitance vs Vds




Figure 9 Power De-rating




Figure 8 Safe Operation Area




Figure 10  $V_{GS(\text{th})}$  vs Junction Temperature





Figure 11 Normalized Maximum Transient Thermal Impedance

**TO-220-3L Package Information**


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.400	4.600	0.173	0.181
A1	2.250	2.550	0.089	0.100
b	0.710	0.910	0.028	0.036
b1	1.170	1.370	0.046	0.054
c	0.330	0.650	0.013	0.026
c1	1.200	1.400	0.047	0.055
D	9.910	10.250	0.390	0.404
E	8.9500	9.750	0.352	0.384
E1	12.650	12.950	0.498	0.510
e	2.540 TYP.		0.100 TYP.	
e1	4.980	5.180	0.196	0.204
F	2.650	2.950	0.104	0.116
H	7.900	8.100	0.311	0.319
h	0.000	0.300	0.000	0.012
L	12.900	13.400	0.508	0.528
L1	2.850	3.250	0.112	0.128
V	7.500 REF.		0.295 REF.	
Φ	3.400	3.800	0.134	0.150